

# uprating options



## Overview of uprating options for leaf-spring Eurochassis

Vehicle type	Maximum uprating		Product
	Rear axle (kg)	GVW (kg)	
<b>YOM 1982-1994 Fiat/Peugeot/Citroen Typ 280/290</b>			
Ducato 10, Boxer J5-1000, Jumper C25-1000	1480	2820	AirLift
Ducato 14 <sup>(1)</sup> , Boxer J5-1400 <sup>(1)</sup> , Jumper C25-1400 <sup>(1)</sup>	1950	3505	AirLift
<b>YOM 1994-2006 Fiat/Peugeot/Citroen Typ 230</b>			
Ducato 10, Boxer 1000, Jumper 1000	1750	3200	AirLift
Ducato 14, Boxer 1400, Jumper 1400	1900	3550	AirLift
<b>YOM 1994-2006 Fiat/Peugeot/Citroen Typ 244</b>			
Ducato 11, Boxer 1100, Jumper 1100	1750	3200	AirLift
Ducato 15, Boxer 1500, Jumper 1500	Unchanged	3500	AirLift
Ducato Maxi, Boxer 1800, Jumper 1800	Unchanged	3850	AirLift

## YOM 2006-. Fiat/Peugeot/Citroen Typ X250 X290 with AirLift Maxi

Versione	Original			Maximum uprating		
	axle load 1	axle load 2	GVW	axle load 1	axle load 2	GVW
A	1630	1650	2935-3000	Unchanged	1900	3300
A	1750	1650	3150	Unchanged	1900 <sup>1); 2)</sup>	3300 <sup>3)</sup>
A	at least 1750	at least 1900	irrelevant	1850 <sup>1)</sup>	2240 <sup>1); 2)</sup>	4090 <sup>3)</sup>
B	at least 1750	at least 1900	irrelevant	1850 <sup>1)</sup>	2240 <sup>1); 2)</sup>	4090 <sup>3)</sup>
C	at least 1750	at least 1900	irrelevant	1850 <sup>1)</sup>	2240 <sup>1); 2)</sup>	4090 <sup>3)</sup>
G	at least 1750	at least 1900	irrelevant	1850 <sup>1)</sup>	2240 <sup>1); 2)</sup>	4090 <sup>3)</sup>
F	1630	at least 1900	2800	Unchanged	1900 <sup>1); 2)</sup>	3100 <sup>3)</sup>
D	at least 1850	at least 2000	irrelevant	2100 <sup>1)</sup>	2510 <sup>1); 2) (bis ET38)</sup>	4610 <sup>3)</sup>
D	at least 1850	mind. 2000	irrelevant	2100 <sup>1)</sup>	2600 <sup>1); 2) (bis ET52)</sup>	4700 <sup>3)</sup>
E	2100	2400 - 2500	3995 - 4300	Unchanged	Unchanged	4400 <sup>3)</sup>
H	2100	2400	3510	Unchanged	Unchanged	4000 <sup>3)</sup>

1) If the factory approval for the loads is already higher, this is retained.

2) The permissible axle load of the vehicle must not be greater than twice the wheel/tire combination.

3) The sum of the axle loads must be greater than or equal to the target permissible total mass of the vehicle.

## Overview of uprating options for leaf-spring MAN TGE Chassis

Front axle (kg)	Original		Maximum uprating (Axle load unchanged)	
	Rear axle (kg)	max GVW (kg)	GVW (kg)	Product
1800	2100	3000	3500	AirLift Maxi
2100	2100	3000	3500	AirLift Maxi
1800	2100	3500	3900	AirLift Maxi
2100	2100	3500	4200	AirLift Maxi
1800	2250	3500	4000	AirLift Maxi
2100	2250	3500	4200	AirLift Maxi
1800	2380	3880	4150	AirLift Maxi
2100	2380	3880	4400	AirLift Maxi
1800	2380	4000	4150	AirLift Maxi
2100	2380	4000	4400	AirLift Maxi

Uprating subject to sufficient load capacity of the wheel/tyre combination.  
Uprating may vary depending on vehicle type.